


COPYRIGHT - 2023 BY LINKO ELECTRIC COPYRIGHT



表一：电气参数/Electrical parameters

芯数	2芯	3芯	4芯	XX芯	XX芯	XX芯
母端 Female						
公端 Male						
额定电流 Rated current	25A	25A				
额定电压 Rated voltage	500V AC	500V AC				
绝缘耐压 (Max) Contact resistance	2000V AC	2000V AC				
绝缘电阻 (Min) Insulation resistance	1.0mΩ	1.0mΩ				
导线规格 Wire gauge	2.5~4.0mm ² /14~12AWG	2.5~4.0mm ² /14~12AWG				
接线方式 Terminator type	☐ 锁线/Screwing					
导线直径 Cable Dia	/					
紧固扭矩 Tightening torque	0.4N.m					
防护等级 IP code	对接状态 ☐ IP65 ☐ IP67 ☒ IP68 ☐ IPx9k					
机械寿命 (Min) Operating cycles	500次					
工作温度 Operating temperature	-40℃ ~ +85℃(金属款/Metal shell)					

表二：“A”尺寸/Length

芯数	2芯	3芯
母端 Female		
A	40.9 "A"±0.5 	40.9 "A"±0.5
公端 Male		
A	40.9 "A"±0.5 	40.9 "A"±0.5

ECN NO.	REV.	MODIFICATION	DATE	DRAWN	APPROVED
N/A	A1	初版发行	2024/01/12	杨今心	宋星亮

编码原则:

Part Number rules

LP-24- X XX XX- X X -X XX X
1 2 3 4 5 6 7 8 9 10

1. 产品系列: 以两个字母表示如LP/DH/BD/YF/YP/YW/YZ/LK...等

Product series is represented by two capital letters such as LP/DH/BD/YF/YP/YW/YZ/LK, etc.

2. 产品型号: 12/16/20/24/28.

Product number

3. 公母类别: C=公针/端 J=母针/端 K=公母混合

Interface type C=male pin/end J=female pin/end K=both male and female pins

4. 接口类别:

Interface type

4.1 电源&信号: 非PIN针=00

Non-pin type=00

PIN针类: 01=单芯 02=2芯 03=3芯 04=4芯....

Pin type: 01=single pin 02=2 pin 03=3 pin 04=4 pin....

4.2 数据&信号类: USB\HDMI\RJ45\ (光纤: LC/FC/SC/ST/MPO/MTP等).

Signal class: USB\HDMI\RJ45\ (optical fiber: LC/FC/SC/ST/MPO/MTP, etc.

数据&信号类范例:

Signal type example: /USB3A/1 0 0

USB 3A: USB 3.0

USB 3B: USB 3.1

其它款依此类推

And so on

0	0接口
1	1接口
2	2接口

0	不防水
1	防水

0	带PCB板
1	带Hsg
2	口朝上
3	直通式
4	口朝下
5	带胶芯
6	胶芯带线

5. 连接器类型 PE=插头 SX=插座 PP=对接插座

Connector Type PE=Plug SX=Receptacle PP=Floating connector

6. 接线方式 0=焊接 1=压接 2=锁线 3=铆接 4=其它

Wiring method 0=Soldering 1=Crimping 2=Screwing 3=Riveting 4=Other

7. 材料属性 1=塑胶+金属 2=全塑胶 3=全金属

Material 1=Plastic+metal 2=All plastic 3=All metal

8. 特殊码 0=插头 1=单孔直式插座 2=两孔法兰插座 4=四孔法兰插座

Special code 0=Plug/Floating connector 1=Single-hole straight receptacle

2=Two-hole flange receptacle 4=Four-hole flange receptacle

9. 流水码Streaming code :01~99

10. 区别码空白或A~Z / Distinction code: blank or A-Z

X.X±0.3 X.XX±0.15 X.XXX±0.100 TOLERANCES UNLESS OTHERWISE SPECIFIED			X°±3° X.X'±1.0° 未注圆角R0.2 SHENZHEN LINKO ELECTRIC CO.,LTD		
DRAWN	杨今心	2024/01/12	TITLE:		
CHECKED	杨武	2024/01/12	LP24四孔法兰插座金属款锁线式		
APPROVED	宋星亮	2024/01/12	P/N:		
UNIT: mm	SIZE: A4	SHEET: 1/1	LP-24-xxxSX-23-4xxx		A1
PORJ.		SCALE /			