


- 编码原则:
Part Number rules
LP-20- X XX XX- X X -X XX X
1 2 3 4 5 6 7 8 9 10
- 产品系列: 以两个字母表示如LP/DH/BD/YF/YP/YW/YZ/LK...等
Product series is represented by two capital letters such as LP/DH/BD/YF/YP/YW/YZ/LK, etc.
 - 产品型号: 12/16/20/24/28.
Product number
 - 公母类别: C=公针/端 J=母针/端 K=公母混合
Interface type C=male pin/end J=female pin/end K=both male and female pins
 - 接口类别:
Interface type
4.1 电源&信号: 非PIN针=00
Non-pin type=00
PIN针类: 01=单芯 02=2芯 03=3芯 04=4芯...
Pin type: 01=single pin 02=2 pin 03=3 pin 04=4 pin....
4.2 数据&信号类: USB\HDMI\RJ45\ (光纤: LC/FC/SC/ST/MP0/MTP等).
Signal class: USB\HDMI\RJ45\ (optical fiber: LC/FC/SC/ST/MP0/MTP, etc.
数据&信号类范例:
Signal type example: /USB3A/1 0 0
USB 3A: USB 3.0
USB 3B: USB 3.1
其它款依此类推
And so on
0 0接口
1 1接口
2 2接口
0 不防水
1 防水
0 带PCB板
1 带Hsg
2 口朝上
3 直通式
5 带胶芯
4 口朝下
6 胶芯带线
5. 连接器类型 PE=插头 SX=插座 PP=对接插座
Connector Type PE=Plug SX=Receptacle PP=Floating connector
6. 接线方式 0=焊接 1=压接 2=锁线 3=铆接 4=其它
Wiring method 0=Soldering 1=Crimping 2=Screwing 3=Riveting 4=Other
7. 材料属性 1=塑胶+金属 2=全塑胶 3=全金属
Material 1=Plastic+metal 2=All plastic 3=All metal
8. 特殊码 0=插头 1=单孔直式插座 2=两孔法兰插座 4=四孔法兰插座
Special code 0=Plug/Floating connector 1=Single-hole straight receptacle
2=Two-hole flange receptacle 4=Four-hole flange receptacle
9. 流水码 Streaming code :01-99
10. 区别码空白或A Z / Distinction code:blank or A-Z

表一: 电气参数/Electrical parameters

芯数	2芯	3芯	4芯	4芯	5芯	7芯	9芯	12芯
母端 Female								
公端 Male								
额定电流 Rated current	20A				10A		5A	
额定电压 Rated voltage					500V AC		250V AC	
耐压 (Max) Dielectric withstanding voltage					2000V AC		1500V AC	
接触电阻 (Max) Contact resistance	1.0mΩ				3.0mΩ		5.0mΩ	
绝缘电阻 (Min) Insulation resistance	500MΩ							
线规 Wire gauge	2.5~4.0mm²/14~12AWG				1.0~1.5mm²/ 18~16AWG		0.34~0.5mm²/22~20AWG	
焊接方式 terminal type	焊接/welding							
线径规格 Cable dia	/							
紧固扭矩 Tightening torque	1.3N.m							
防护等级 IP-code	对接状态 ☐ IP65 ☐ IP67 ☒ IP68 ☐ IPx9k							
机械寿命 (Min) Operating cycles	500次							
工作温度 Operating temperature	-40℃ ~ +85℃(金属款/Metal shell)							

X.X±0.3 X.XX±0.15 X.XXX±0.100			X°±3° X.X°±1.0° 未注圆角R0.2			TOLERANCES UNLESS OTHERWISE SPECIFIED		
DRAWN		杨今心		2024/03/18		TITLE: LP20型xx芯单孔直式x插座金属款 焊接式		
CHECKED		杨武		2024/03/18		P/N: LP-20-xxxSX-03-1xxx		
APPROVED		宋星亮		2024/03/18				
UNIT: mm		SIZE:A4		SHEET:1/2				
PORJ.				SCALE /		A1		



表二: "A"尺寸/Length

母端 Female	2芯	3芯	4芯	4芯	5芯	7芯	9芯	12芯
A	28.1	31.9	28.2	28.3	26.3	26.4	27.3	27.5
公端 Male	2芯	3芯	4芯	4芯	5芯	7芯	9芯	12芯
A	28.4	31.9	28.4	28.3	26.7	26.7	26.3	26.3

X.X±0.3X.XX±0.15X.XXX±0.100 X°±3°X.X°±1.0°未注圆角R0.2 TOLERANCES UNLESS OTHERWISE SPECIFIED			LINKO 深圳市凌科电气有限公司 SHENZHEN LINKO ELECTRIC CO.,LTD	
DRAWN	杨今心	2024/03/18	TITLE: LP20型xx芯单孔直式x插座金属款 焊接式	
CHECKED	杨武	2024/03/18		
APPROVED	宋星亮	2024/03/18		
UNIT: mm	SIZE:A4	SHEET:2/2	P/N:	
PORJ.		SCALE /	LP-20-xxxSX-03-1xxx	