





THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN LINKO ELECTRIC PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM LINKO CORP.



7	8	9	10
ECN NO.	REV.	MODIFICATION	DATE
ECNXXXXXX	A1	初版发行	2024/03/11

编码原则:
 Part Number rules
 LP-12- X XX XX- X X -X XX X
 1 2 3 4 5 6 7 8 9 10
 1. 产品系列: 以两个字母表示如LP/DH/BD/YF/YP/YW/YZ/LK...等
 Product series is represented by two capital letters such as LP/DH/BD/YF/YP/YW/YZ/LK, etc.
 2. 产品型号: 12/16/20/24/28.
 Product number
 3. 公母类别: C=公针/端 J=母针/端 K=公母混合
 Interface type C=male pin/end J=female pin/end K=both male and female pins
 4. 接口类别:
 Interface type

4.1 电源&信号:非PIN针=00
 Non-pin type=00
 PIN针类: 01=单芯 02=2芯 03=3芯 04=4芯....
 Pin type:01=single pin 02=2 pin 03=3 pin 04=4 pin....
 4.2 数据&信号类: USB\HDMI\RJ45\ (光纤: LC/FC/SC/ST/MPO/MTP等).
 Signal class: USB\HDMI\RJ45\ (optical fiber: LC/FC/SC/ST/MPO/MTP, etc.
 数据&信号类范例:
 Signal type example: /USB3A/1 0 0

USB 3A: USB 3.0	0	0接口	0	不防水	0	带PCB板
USB 3B: USB 3.1	1	1接口	1	防水	1	带Hsg
其它款依此类推	2	2接口			2	口朝上
And so on					3	直通式
					4	口朝下
					5	带胶芯
					6	胶芯带线

表一: 电气参数/Electrical parameters

	2芯	3芯	4芯	5芯	6芯	7芯	8芯
母端 Female							
公端 Male							
额定电流 Rated current	5A				3A		
额定电压 Rated voltage	125V AC				100V AC		
耐压 (Max) Dielectric withstanding voltage	1500V AC				1000V AC		
接触阻抗 (Max) Contact resistance	5mΩ						
绝缘阻抗 (Min) Insulation resistance	500MΩ						
线规 Wire gauge	0.34~0.5mm ² /22~20AWG				0.25~0.34mm ² /24~22AWG		
接线方式 Terminal type	□ 焊接/welding						
线缆直径 Cable OD	□ φ3.5 ~ φ4.5mm		□ φ4.5 ~ φ5.5mm		□ φ5.0 ~ φ6.5mm		
紧固扭矩 Tightening torque	0.8N.m						
防护等级 IP code	对接状态 □ IP65 □ IP67		□ IP68		□ IPx9k		
机械寿命 (Min) Operating cycles	500次						
工作温度 Operating temperature	-25°C ~ +85°C(标准塑胶款); -40°C ~ +85°C(定制塑胶款)						

- 连接器类型 PE=插头 SX=插座 PP=对接插座
Connector Type PE=Plug SX=Receptacle PP=Floating connector
- 接线方式 0=焊接 1=压接 2=锁线 3=铆接 4=其它
Wiring method 0=Soldering 1=Crimping 2=Screwing 3=Riveting 4=Other
- 材料属性 1=塑胶+金属 2=全塑胶 3=全金属
Material 1=Plastic+metal 2=All plastic 3=All metal
- 特殊码 0=插头 1=单孔直式插座 2=两孔法兰插座 4=四孔法兰插座
Special code 0=Plug/Floating connector 1=Single-hole straight receptacle 2=Two-hole flange receptacle 4=Four-hole flange receptacle
- 流水码 Streaming code :01-99
- 区别码空白或A ~Z / Distinction code:blank or A-Z

X.X±0.3 X°±3° X.XX±0.15 X.X°±1.0° X.XXX±0.100 未注圆角R0.2 TOLERANCES UNLESS OTHERWISE SPECIFIED		 深圳市凌科电气有限公司 SHENZHEN LINKO ELECTRIC CO.,LTD	
DRAWN	杨今心	2024/03/11	TITLE:
CHECKED	杨武	2024/03/11	LP12型xx芯对接x插座塑胶款焊接式
APPROVED	宋星亮	2024/03/11	
UNIT: mm	SIZE:A4	SHEET:1/1	P/N:
PORJ.		SCALE /	LP-12-xxxPP-02-0xxx
			A1