



COPYRIGHT - 2023

BY LINKO ELECTRIC COPYRIGHT



安装开孔尺寸
Mounting hole size
安装板推荐使用厚度(Max): 3.0mm
Recommended thickness of mounting plate



表一: 电气参数/Electrical parameters

芯数	3芯	3芯	3芯	4芯	10芯	12芯	19芯	24芯
母端 Female								
公端 Male				长针 				
额定电流 Rated current	25A	35A	45A	25A	10A	10A	5A	5A
额定电压 Rated voltage	500V AC	300V AC	230V AC	500V AC	400V AC	400V AC	250V AC	250V AC
耐压 (Max) Dielectric withstanding voltage	2000V AC	1500V AC	1500V AC	2000V AC	2000V AC	2000V AC	1500V AC	1500V AC
接触电阻 (Max) Contact resistance	1.0mΩ	1.0mΩ	1.0mΩ	1.0mΩ	3mΩ	3mΩ	5mΩ	5mΩ
绝缘电阻 (Min) Insulation resistance	500MΩ	500MΩ	500MΩ	500MΩ	500MΩ	500MΩ	500MΩ	500MΩ
线规 Wire gauge	2.5*4.0mm ² /14*12AWG	6.0*8.0mm ² /10*8AWG	8(电源)~10(电子)mm ² /8-6AWG	2.5*4.0mm ² /14*12AWG	1.0*1.5mm ² /18*16AWG	1.0*1.5mm ² /18*16AWG	0.34*0.5mm ² /22*20AWG	0.34*0.5mm ² /22*20AWG
接线方式 Terminal Type	☐ 焊接/welding							
线径直径 Cable Ø	/							
紧固扭矩 Tightening torque	1.5N.m							
防护等级 IP code	对接状态 ☐ IP65 ☐ IP67 ☒ IP68 ☐ IPx9k							
机械寿命 (Min) Operating cycles	500次							
工作温度 Operating temperature	-40°C ~ +85°C(金属款/Metal shell)							

ECN NO.	REV.	MODIFICATION	DATE	DRAWN	APPROVED
N/A	A1	初版发行	2024/01/12	杨今心	宋星亮

编码原则:

Part Number rules

LP-24- X XX XX- X X -X XX X
1 2 3 4 5 6 7 8 9 10

1. 产品系列: 以两个字母表示如LP/DH/BD/YF/YP/YW/YZ/LK...等

Product series is represented by two capital letters such as LP/DH/BD/YF/YP/YW/YZ/LK, etc.

2. 产品型号: 12/16/20/24/28.

Product number

3. 公母类别: C=公针/端 J=母针/端 K=公母混合

Interface type C=male pin/end J=female pin/end K=both male and female pins

4. 接口类别:

Interface type

4.1 电源&信号: 非PIN针=00

Non-pin type=00

PIN针类: 01=单芯 02=2芯 03=3芯 04=4芯....

Pin type: 01=single pin 02=2 pin 03=3 pin 04=4 pin....

4.2 数据&信号类: USB\HDMI\RJ45\ (光纤: LC/FC/SC/ST/MP0/MTP等).

Signal class: USB\HDMI\RJ45\ (optical fiber: LC/FC/SC/ST/MP0/MTP, etc.

数据&信号类范例:

Signal type example: /USB3A/1 0 0

USB 3A: USB 3.0

USB 3B: USB 3.1

其它款依此类推

And so on

0	0接口
1	1接口
2	2接口

0	不防水
1	防水

0	带PCB板
1	带Hsg
2	口朝上
3	直通式
4	口朝下
5	带胶芯
6	胶芯带线

5. 连接器类型 PE=插头 SX=插座 PP=对接插座

Connector Type PE=Plug SX=Receptacle PP=Floating connector

6. 接线方式 0=焊接 1=压接 2=锁线 3=铆接 4=其它

Wiring method 0=Soldering 1=Crimping 2=Screwing 3=Riveting 4=Other

7. 材料属性 1=塑胶+金属 2=全塑胶 3=全金属

Material 1=Plastic+metal 2=All plastic 3=All metal

8. 特殊码 0=插头 1=单孔直式插座 2=两孔法兰插座 4=四孔法兰插座

Special code 0=Plug/Floating connector 1=Single-hole straight receptacle

2=Two-hole flange receptacle 4=Four-hole flange receptacle

9. 流水码 Streaming code :01-99

10. 区别码空白或A ~Z / Distinction code: blank or A-Z

X.X±0.3 X.XX±0.15 X.XXX±0.100 TOLERANCES UNLESS OTHERWISE SPECIFIED			X°±3° X.X'±1.0° 未注圆角R0.2 SHENZHEN LINKO ELECTRIC CO.,LTD		
DRAWN	杨今心	2024/01/12	TITLE:		
CHECKED	杨武	2024/01/12	LP24单孔直式插座金属款焊接式		
APPROVED	宋星亮	2024/01/12	P/N:		
UNIT: mm	SIZE:A4	SHEET:1/2	LP-24-xxxSX-03-1xxx		
PORJ.		SCALE /	A1		

THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN LINKO ELECTRIC PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM LINKO CORP.














1
COPYRIGHT - 2023

2
BY LINKO ELECTRIC COPYRIGHT

3

7 ECN NO.	REV.	8 MODIFICATION	9 DATE	10 DRAWN	APPROVED
N/A	A1	初版发行	2024/01/12	杨今心	宋星亮

表二: "A"尺寸/Length

芯数	3芯_25A	3芯_35A	3芯	4芯	10芯	12芯	19芯	24芯
母端 Female								
A	37.0 	41.0 		37.5 	31.7 	31.7 	32.6 	32.6 
公端 Male				长针 				
A	37.0 	40.3 		37.5 	31.1 	31.1 	32.6 	32.6 

X.X±0.3 X.XX±0.15 X.XXX±0.100 TOLERANCES UNLESS OTHERWISE SPECIFIED			X°±3° X.X'±1.0° 未注圆角R0.2			 深圳市凌科电气有限公司 SHENZHEN LINKO ELECTRIC CO.,LTD	
DRAWN	杨今心	2024/01/12	TITLE: LP24单孔直式插座金属款焊接式				
CHECKED	杨武	2024/01/12					
APPROVED	宋星亮	2024/01/12					
UNIT: mm	SIZE:A4	SHEET:2/2	P/N: LP-24-xxxSX-03-1xxx				A1
PORJ.		SCALE /					